



## China abec 7 Bearings Supplier



6330 Bearing 2D drawings and 3D CAD models

Distributor Wholesale Clutch Ball Bearing  
 Motorcycle Spare Parts SKF NTN Koyo Timken  
 NACHI 6330 6006 6202 6204 6208 6302 6304  
 Deep Groove Ball Bearing

Bearing No. 6330

|                               |                  |
|-------------------------------|------------------|
| Size                          | 150x320x65 mm    |
| Bore Diameter                 | 150 mm           |
| Outer Diameter                | 320 mm           |
| Width                         | 65 mm            |
| d                             | 150 mm           |
| D                             | 320 mm           |
| B                             | 65 mm            |
| C                             | 65 mm            |
| r min.                        | 4 mm             |
| da min.                       | 168 mm           |
| Da max.                       | 302 mm           |
| ra max.                       | 3.0 mm           |
| Weight                        | 26.2 Kg          |
| Basic dynamic load rating (C) | 274 kN           |
| Basic static load rating (C0) | 284 kN           |
| (Grease) Lubrication Speed    | 2000 r/min       |
| Enclosure                     | Open             |
| Bore Type                     | Cylindrical Bore |
| Configuration                 | Single Row       |
| Bore Size                     | 150 mm           |
| Outside Diameter              | 320 mm           |
| Width                         | 65 mm            |
| Fillet Radius/Chamfer         | 4 mm             |
|                               |                  |



## China abec 7 Bearings Supplier

|                         |                   |
|-------------------------|-------------------|
| Dynamic Load Rating     | 274,000 N         |
| Static Load Rating      | 284,000 N         |
| Limiting Speed - Grease | 2,100 rpm         |
| Limiting Speed - Oil    | 2,400 rpm         |
| Factor fo               | 13.9              |
| Radial Clearance        | 0.018 to 0.053 mm |
| da (min)                | 168 mm            |
| Da (max)                | 302 mm            |
| ra (max)                | 3 mm              |